



# Biglift 2.65 Saaa 230 VW

Electro-hydraulic twin-ram lift 6.5 t with swivel arm superstructure



**VAS 782 049 | ASE78204980000:**  
**20012135-1 & 20012135-2**

| Order no.  | Item no. | # | Part of the approval according to order no. 20012135-1/-2:                                    |
|------------|----------|---|---|
| 20012135-1 | 21209    | 1 | Swivel arm superstructure 2.65 Saaa 230, incl. 4 single telescopic lifting pads 16008, Ø50 mm |
|            | 12567    | 1 | VW specification VAS 782049   |
|            | 11103    | 1 | Document holder   |
|            | 11104    | 1 | Set of 2 magnetic tool trays  |
| 20012135-2 | 16010    | 4 | Lifting pad extension 50 mm - Ø50 mm 1 pc.  |
|            | 10276    | 1 | Hydraulic unit BL Sa 6,5 t, PD 2150, stroke 1860 mm   |
|            | 11063    | 1 | Set of cables 10 m  |
|            | 12036    | 1 | Ecological hydraulic fluid 17 ltr.  |

Biglift 2.65 Saaa 265 – VAS 782 049 | ASE782049800000

The triple telescopic swivel arms convince with an **unconventional lifting area**, especially suited for utility vehicles and large passenger cars.

The **internal arm locking system** installed as standard reliably protects against external influences.

The **strong 213 mm diameter cylinders** are also designed for long-lasting functionality and further round off high quality level which ensures **low maintenance requirements**.

Even in the event of a power blackout the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Biglift 2.65 Saaa 230 is perfectly completed by a **control system that is both visually and technically convincing**.

**Standard colour:**  
RAL 7012

**Options:**  
Wide range of extra pads, depending on vehicle type

**Installation variants:**  
Superstructure on floor  
Ceiling installation

Not included in the scope of approval, please order separately:

**Steel cassette:**  
Standard: painted  
Optional: hot-dip galvanized, plastic coated

