



# Biglift 4.55 Combi VW

Electro-hydraulic 2x4-ram lift 5.5 t, platforms and free-wheel lift with arms



**VAS 782 027A | ASE78202781000:**  
**20012134-1 & 20012134-2**

Order no.	Item no.	#	Part of the approval according to order no. 20012134-1/-2:
20012134-1	21509	1	Platform superstructure 4.55 Fn 550 Combi
	21205	1	Swivel arm superstructure 4.55 Saav 155 Combi, incl. lifting pads 11028, minimum height 135 mm, Ø 50 mm, with Ø 50 – 40 mm reducers
	12566	1	VW specification VAS 782027A
	16010	4	Pad extensions 50 mm - Ø50 mm 1 pc.
	21100	1	Drive-on ramp on floor 1100 mm 10°, 1 set = 2 pcs.
	21084	1	Roll-off safety device, H = 100 mm, 1 set = 2 pcs.
	12942	1	LED lighting for vehicle bottom, 3 pcs. per platform
	11103	1	Document holder
	11104	1	Set of 2 magnetic tool trays
	21080	1	Power distribution for 1 platform (Schuko plug 230 V / 16 A / IP54)
	21096	1	Pneumatic installation for 1 platform (1 T-piece each front and back)
20012134-2	10295	1	Hydraulic unit BL 4.55-1240/1850-Combi on floor or in floor without flush floor device
	11071	1	Set of cables JE 10 m
	12038	1	Ecological hydraulic fluid 20 ltr

The Biglift 4.55 Combi is optimally suited for **quick and easy vehicle lifting**.

The platforms are constructed of very strong and rigid **solid steel** that offers a **high degree of stability**. The additional swivel arms, which come with **double telescopic and crosswise adjustable swivel arms as standard**, make the Biglift 4.55 Combi the perfect helper in your workshop.

2x4 **strong mm diameter cylinders** are also designed for long-lasting functionality and further round off the high quality level which ensures **low maintenance requirements**.

Even in the event of a power blackout the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Biglift 4.55 Combi is perfectly completed by a **control system that is both visually and technically convincing**.

### Standard colour:

RAL 7012

### Options:

Wide range of extra pads, depending on vehicle type

### Installation variants:

Superstructure on floor

Superstructure in floor with or without flush floor device

Not included in the scope of approval, please order separately:

### Steel cassette:

Standard: painted

Optional: hot-dip galvanized or plastic coated

