

Masterlift 2.35 Saa

Electro-hydraulic twin-ram lift, 3.5 t capacity, superstructure with arms



Application

- Repairs and maintenance
- Body work

Approvals / recommendations

- BMW / Mini:
- Rolls-Royce:
- Volkswagen Group:
- Volvo:
- Masterlift 2.35 Saa 230
- Mercedes-Benz:
- Masterlift 2.35 Saa 260
- Renault

Description:

Steel cassette:

- Waterproof steel cassette

Hydraulic unit:

- Hard-chrome plated cylinder
- Flexible synchronization and safety system
- Corrosion-free guiding elements
- Pump unit with immersed motor
- Hydraulic oil
- Pneumatic emergency lowering
- Programmable pushbutton control unit

Superstructure:

- Double-telescopic arms
- Internal arm locking system
- Low minimum height - perfect for sports cars - with a minimum height under 100 mm

Standard colours:

- Base plates: RAL 7016 - grey
- Arms: RAL 3020 - red

Versions:

Steel cassette:

- Zinc-coated
- Coated
- Self-carrying

Installation:

- Superstructure on floor
- Superstructure in floor
- Ceiling installation

Versions:

- Saa 230 & Saa 260
also available as
Sport & Universal versions

Optional extras:

- Large program of extra pads

Zinc coating and special colours on request!



Click the QR-Code for detailed product information.

Further Information on www.autopstenhoj.com

AUTOPSTENHOJ GmbH

Sandkampstraße 90
D-48432 Rheine
☎ +49 5971 8602-02
✉ info@autopstenhoj.com

AUTOPSTENHOJ GmbH

Barrit Langgade 188-190
DK-7150 Barrit
☎ +45 76 82 13 30
✉ info@autopstenhoj.com

Technical data	
Lifting capacity	3,500 kg
Lifting height	Saa 230: 1,950 mm Saa 260: 1,900 mm
Working height	Saa 230: 2,045 - 2,124 mm Saa 260: 1,995 - 2,074 mm
Cylinder diameter	Saa 230: 2 x 123 mm Saa 260: 2 x 140 mm
Distance between cylinders	Saa 230: 2,285 mm Saa 260: 2,600 mm
Lifting / lowering time (high pressure)	approx. 30 sec.
Foundation depth	2,625 mm
Pump unit	3 kW
Hydraulic oil	10 l
Voltage	230 / 400 V – 50 Hz – 16 A

Arm superstructure	
Total width	3,000 mm
Lifting pad included in the delivery	Uni: 16007 (95-174 mm) Sport: 16006 (78-110 mm)
Min. height	Uni: 95 - 174 mm Sport: 78 - 110 mm + 50 mm height extension
Drive-through width	Saa 230: 2,160 mm Saa 260: 2,455 mm
Arm length, min. - max.	658 – 1,313 mm

