

Biglift 2.55 Saa 265 VW

Electro-hydraulic twin-ram lift 5.5 t with swivel arm superstructure





Order no.	Item no.	#	Part of the approval according to order no. 20012133-1/-2:
20012133-1	21203	1	Superstructure 2.55 Saa 265 Ø213, incl. 4 single telescopic lifting pads 16008, Ø 50mm
	12565	1	VW specification VAS 782037A
	11103	1	Document holder
	11104	1	Set of 2 magnetic tool trays
	16010	4	Lifting pad extension 50 mm – Ø50 mm 1 pc.
20012133-2	11063	1	Set of cables 10 m
	10309	1	Hydraulic unit BL PD 2650 mm, stroke 1860 mm, cyl. Ø 213 mm
	12036	1	Ecological hydraulic fluid 17 ltr.

The double telescopic swivel arms convince with an unconventional lifting area, especially suited for utility vehicles and large passenger cars.

The internal arm locking system installed as standard reliably protects against external influences. An integrated mechanical safety ratchet offers additional safety for all working procedures.

The strong 213 mm diameter cylinders are also designed for long-lasting functionality and further round off high quality level which ensures low maintenance requirements.

Even in the event of a power blackout the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

Freigabe Nr. VAS 782 037A

The Biglift 2.55 Saa 265 is perfectly completed by a control system that is both visually and technically convincing.

Standard colour:

RAL 7012

Options:

Wide range of extra pads, depending on vehicle type

Installation variants:

Superstructure on floor Ceiling installation

Not included in the scope of approval, please order separately: Steel cassette:

Standard: painted

Optional: hot-dip galvanized, plastic coated

